

LIMITED WARRANTY

Solid Partitions HDPE products are warranted by the manufacturer for period of Twenty-five (25) years against delamination and breakage from the date of substantial completion. If material is deemed defective by the manufacturer during this period, then it shall be replaced free of charge.

All warranty claims are for material only and do not include installation costs.

This limited warranty is subject to the following conditions:

1. The warranted products have been installed in accordance with the manufacturer's written instructions and drawings supplied with the original order.
2. The limited warranty only applies to the original installation. No modifications or altered installations allowed without prior manufacturer consent.
3. The limited warranty shall not be applicable if the defect has resulted from vandalism, neglect, or improper handling of materials.

Any claim under such warranties must be made during the warranty period and shall be asserted by contacting your local distributor or the factory direct.

Solid Partitions
W233 N2830 Roundy Circle W
Pewaukee, WI 53072
Phone# 414-763-0029

CARE & MAINTENANCE

Cleaning Methods

Solid Partitions HDPE is shipped with a clear protective coating that is to be removed after installation is completed. In some cases, a slight residue may remain after the protective coating is removed. This can be removed by simply cleaning all surfaces with water and a mild liquid soap. For removal of tougher residue, a mild solvent or graffiti remover may be used. Never use abrasive pads or abrasive cleaners as these may damage the HDPE and void the limited warranty. For removal of small scratches, use the blunt end of a screw driver or similar tool and work the scratched material back into the affected area.

Everyday Care & Maintenance

A standard cleaning should be performed on a regular basis with a soft damp cloth. All components should be wiped down and dried. Check and tighten all screws they may have loosened due to vibration or attempted vandalism. Clean and lubricate all hinges with a non-drying lubricant or marine grade white lithium grease.

SolidPartitions